

mass integrated

global part distribution • product lifecycle partner
excess inventory management • value-ad service provider



Data sheet provided by Mass Integrated

massintegrated.com • displayalliance.com

Please call +1.978.465.6190
Email: sales@massintegrated.com



ISO 9001: 2008

Mass Integrated complies with all DMCA takedown notices. Please send a formal DMCA Takedown Notice to Mass Integrated Systems, Inc. • 18 Henry Graf Jr. Road, Unit 1 • Newburyport, MA 01950.

Product Number: NL8060BC21-04

8.4 inches SVGA for Industrial applications

Model number	NL8060BC21-04	Screen size	8.4 inches (21 cm diagonal)
Drive method	a-Si TFT active matrix	Effective display area	170.4 (H) x 127.8 (V) mm
Number of pixels	800 x 600	Pixel arrangement	RGB vertical stripe
Pixel pitch	0.213 (H) x 0.213 (V) mm	Display colors	262K colors
Luminance	400cd/m ²	Contrast	600:1
Viewing angle (*1)	Up: 80°, down: 60° right: 80°, left: 80°	Response speed (*2)	25ms
Input signal	CMOS (RGB 6 bits each)	Back light	One side, 2 CCFL
Power supply voltage	3.3V / 5.0V	Power consumption (*3)	5.5 W
Operating temperature	-20°C to +70°C	Storage temperature	-30°C to +80°C
Polarizer surface	Clear	Inverter	Sold separately * Recommended inverter: 84PW031 / 84PW041
Dimensions	200.0 (W) x 152.0 (H) x 11.0 max. (D) mm	Weight	330g

(*1) Contrast of 10:1 or higher

(*2) Value of Ton+Toff(10% < - > 90%)

(*3) Value does not include power consumption of recommended inverter

All values are typical values (except for the thickness dimension).
All specifications shown on this web site are subject to change without notice.